

Foreverest Resources Ltd

松焦油

250

松焦油呈粘性液体，颜色棕黄至深棕。经过脱水或蒸馏后可用于浸渍船用电缆、橡胶增塑剂、嵌缝胶和医药等。从非充脂木材制得的松焦油呈棕黑色粘稠液体，经蒸馏后可制得木杂酚油、愈创木酚等副产品。

Substance Identification

Synonyms	木焦油
CAS	N/A
EINECS	232-374-8
FEMA	N/A

HS.CODE	380700
Molecular Formula	N/A
Molecular Weight	N/A

Application & Uses

- 浸渍船用电缆
- 橡胶增塑剂
- 嵌缝胶
- 制药成分
- 制备木杂酚油、愈创木酚
- 香皂

Sales Specification

ITEM	VALUE
外观	深棕色粘稠液体
相对密度[ρ]@ d20/4	1.01 to 1.06
粘度[S, 100ml, @85°C]	250 to 350
砷含量 (%)	0.50 max

ITEM	VALUE
机械杂质 (%)	0.50 max
水分 (%)	0.50 max

Similar Specs

Wood Tar Oil

Package

- 镀锌铁桶, 190公斤, 80桶每20尺柜
- IBC集装吨桶, 0.95吨

GHS Hazard Statements

Storage

- 远离火苗、明火、火源
- 单独贮存于仓库
- 仓库地面应备有接地材料
- 密封贮存于通风、干燥、阴凉处，避免阳光直射
- 避免人体直接接触
- 远离儿童、动物

Relation Products

- [Wood Creosote Oil](#)

Relation Articles

- [Building an Industrial Wood Coating Finish](#)
 - [Real Bio-based Ingredients for Formulator's Toolbox](#)
 - [Biopesticide Controls of Plant Diseases: Resources and Products for Organic Farmers in Ohio](#)
-

Remark

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers' requirement and us, if there are any changes, the latest specification will be executed and confirmed in the contract.

Manage consent