

Foreverest Resources Ltd

粗制妥尔油

粗制妥尔油又称液体松香，是硫酸盐制法的副产品。金属加工液中粗制妥尔油常用于乳化液、微乳液，作为辅助乳化剂可以减少主乳化剂的用量，与常用的油酸相比乳化速度快、润滑性优越、清洗效果好并且有一定的抗泡作用，对硬水的适应范围宽，有良好的抗酸败性。粗制妥尔油还被广泛应用于肥皂、清漆、油漆、油墨、润滑剂、金属加工用的油、消毒剂或胶粘剂等领域。 我司供应的北美产粗浮油，主要供应往亚洲、西亚、中东等地。

Substance Identification

Synonyms	CTO 粗浮油 粗制塔尔油
CAS	N/A
EINECS	232-304-6
FEMA	N/A

HS.CODE	380300
Molecular Formula	N/A
Moleclar Weight	N/A

Application & Uses

- 应用于金属扎的金属加工液
- 矿石浮选剂
- 环保染料的缓蚀成分
- 钻油生产
- 混凝土制品分离液

Sales Specification

ITEM	VALUE
酸值□mgKOH/g□	≥140
湿气含量 (%)	≤0.5
松香酸含量 (%)	≤32.0
不皂化物 (%)	≤4.0

Package

- 集装箱液袋，22吨

GHS Hazard Statements

此产品在暂无可用数据，[点击查看UNECE对GHS的统一分类和标签管理制度](#)

Storage

- 避免与皮肤和眼睛直接接触
- 不允许排放到含酸的管道
- 远离火苗、明火和火源。避免儿童或动物接近
- 避免阳光直射，贮存在阴凉、干燥处
- 贮存于通风处

Relation Products

- [Tall Oil Fatty Acid](#)
- [Tall Oil Pitch](#)
- [Tall Oil Rosin](#)

Remark

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers' requirement and us, if there are any changes, the latest specification will be executed and confirmed in the contract.

Manage consent