

Foreverest Resources Ltd

真空电镀树脂

FR170

FR170树脂专门应用于真空电镀，对各类塑胶基材、金属镀层或不锈钢具有良好的附着力。对TDI改性醇酸树脂有良好的相容性，并可在120#溶剂中溶解。

Substance Identification

Synonyms	
CAS	N/A
EINECS	N/A
FEMA	N/A

HS.CODE	N/A
Molecular Formula	N/A
Moleclar Weight	N/A

Application & Uses

- 专门应用于BS□HIPS等底材的真空电镀

Features & Benefits

- 高软化点
- 高硬度
- 高光泽
- 和TDI改性醇酸树脂良好相容
- 可在120#溶剂中溶解
- 对HIPS□ABS和镀膜有良好的附着性

Sales Specification

ITEM	VALUE
酸值□mgKOH/g□	≤20~30
颜色□Gardner□	8~10
软化点□R&B□°C□	170±5

Package

- 镀锌铁桶，25公斤，内衬聚氟乙烯□PVF□防腐蚀涂层
- 镀锌铁桶，50公斤，内衬聚氟乙烯□PVF□防腐蚀涂层
- 镀锌铁桶，500公斤，内衬聚氟乙烯□PVF□防腐蚀涂层

GHS Hazard Statements

Storage

- 避免光线直照
- 和氧化物隔离贮存
- 贮存和运输方式须符合当地法律法规要求
- 贮存在阴凉、干燥处

- 密封贮存

Relation Products

- Colorless Fully Hydrogenated Rosin
- Water-White Hydrogenated Rosin

Remark

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers' requirement and us, if there are any changes, the latest specification will be executed and confirmed in the contract.