

# Foreverest Resources Ltd

---

## 道路标示用树脂

道路标示用树脂，具有淡色、中度软化点等特点，并改善了光照稳定性。特别适合应用于沥青路面和水泥路面等道路标示用的涂料之中。

---

## Substance Identification

### Synonyms

CAS	N/A
EINECS	N/A
FEMA	N/A
HS.CODE	391110

Molecular Formula	N/A
Molecular Weight	N/A

## Application & Uses

- 应用于路面标示涂料原料

## Features & Benefits

- 耐摩擦
- 良好的粘性和热稳定性
- 良好的光反射值
- 耐热耐寒
- 易与其他溶剂相容

## Sales Specification

ITEM	VALUE
酸值[mgKOH/g]	≤25
颜色[Gardner]	≤4

ITEM	VALUE
相对密度（在25°C条件下）	1.09
比重（在25°C条件下）	1.060~1.090
软化点 <small>[R&amp;B]</small> °C	100~110
蒸汽压值（在20°C条件下）mmHg	<0.001
V.O.C含量检测, at 180°C, 6 hours	≤0.5 without smoke and odors

## Package

- 塑料复合纸袋, 25公斤, 640袋 (约16吨) / 20尺柜

## GHS Hazard Statements

## Storage

- 远离火苗、明火和火源
- 注意防尘
- 密封贮存

- 贮存于室温、干燥、阴凉处

## Remark

*The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers' requirement and us, if there are any changes, the latest specification will be executed and confirmed in the contract.*

Manage consent