

Foreverest Resources Ltd

松香甘油酯（工业级）

G1004

工业级松香甘油酯，因其极性和聚合物相容性的特点，赋予大多数基质以优异的特异粘合性。其低分子质量的特性结合脂环族和芳香族结构，使松香树脂能够作为增粘剂兼容绝大多数胶黏剂。工业级松香甘油酯同样可被广泛应用在EVA、丙烯酸树脂、聚氨酯、SIS和SBS等聚合物。

Substance Identification

Identification	Value
Synonyms	Ester Gum Glycerol Ester of Gum Rosin GEGR
CAS	N/A
EINECS	232-482-5
FEMA	N/A

HS.CODE	38069000
Molecular Formula	N/A
Moleclar Weight	N/A

Application & Uses

- 通过与植物油聚合应用于酚醛树脂涂料
- 应用于工业级热熔胶、压敏胶等各类胶黏剂

Sales Specification

ITEM	VALUE
酸值□mgKOH/g□	10 max
软化点□R&B□°C□	98 to 102
颜色□Fe-co Scale□	2 to 4
溶解性	可溶于苯

Similar Specs

- [Glyceryl Rosinate \(Food\)](#)
- [Glyceryl Rosinate \(Food\)](#)
- [Glyceryl Rosinate \(Industrial\)](#)

Package

- 破碎块状，纤维复合纸板桶，50公斤
- 破碎块状，纤维复合纸板桶，250公斤
- 颗粒状、塑料复合纸袋，25公斤，内附PE膜

GHS Hazard Statements

Storage

- 远离热源，火花和明火
- 注意防尘
- 密封贮存
- 贮存于室温、通风、阴凉处
- 避免直接人体接触

Relation Products

- [Colorless Glyceryl Hydrogenated Rosinate](#)
- [Glyceryl Hydrogenated Rosinate \(Industrial\)](#)

Remark

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers' requirement and us, if there are any changes, the latest specification will be executed and confirmed in the contract.