

Foreverest Resources Ltd

醇溶性树脂

AE130200

醇溶性树脂作为衍生物树脂由不饱和酸改性松香与多元醇部分酯化而得。被广泛应用于醇溶性凹版印刷油墨、上光油、涂料、水基油墨等领域。

Substance Identification

Synonyms	ASRR
CAS	N/A
EINECS	N/A
FEMA	N/A

HS.CODE

38069000

Molecular Formula

N/A

Molecular Weight

N/A

Application & Uses

- 醇溶性凹版印刷油墨
- 上光油
- 涂料
- 水基油墨

Features & Benefits

- 优越的醇溶性
- 高光泽
- 高硬度
- 高软化点
- 不易泛黄

Sales Specification

ITEM	VALUE
外观	颗粒或片状
酸值[mgKOH/g]	190~210
颜色[Fe-Co]	≤8
软化点[R&B]°C	125~135
溶解度（1:1相溶于酒精）	clear

Similar Specs

[Alcohol Soluble Rosin Resin](#)

[Alcohol Soluble Rosin Resin](#)

[Alcohol Soluble Rosin Resin](#)

Package

- 塑料复合纸袋，25公斤，640袋（约计16吨）每20尺柜

GHS Hazard Statements

Storage

- 避免光线直照
- 和氧化物隔离贮存
- 贮存和运输方式须符合当地法律法规要求
- 贮存在阴凉、干燥处
- 密封贮存

Relation Products

- [Liquid Terpene Resin](#)
- [Road Marking Resins](#)

Remark

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers' requirement and us, if there are any changes, the latest specification will be executed and confirmed in the contract.

