

Foreverest Resources Ltd

Wood Based Activated Carbon (Water Treatment Uses)

WWT

WWT is a form of wood based activated carbon used for water treatment. It is produced by chemical activation of sawdust using unique phosphoric process.

Substance Identification

Synonyms	Activated Charcoal
CAS	N/A
EINECS	231-153-3
FEMA	N/A

HS.CODE	380210
Molecular Formula	C
Moleclar Weight	12.01

Application & Uses

- Water treatment

Sales Specification

ITEM	VALUE
Adsorption of Methylene Blue, ml/0.1g	10 to 12 min
Adsorption of Iodine, mg/g	900 to 1000 min
LOD Value, %	10 max
PH Value	4 to 11
Particle Size, 200 mesh, %	90 min

Package

- Plastic bag with inner film, 20kg net each

GHS Hazard Statements

There is currently no available data for this product, click to view [GHS Classification and Labelling by UNECE](#).

Storage

- Keep away from heat, sparks and open flame. Guard against dust accumulation of this material
- Keep containers closed when not in use. Store at ambient temperature and atmospheric pressure
- Keep container tightly closed. Keep out of the reach of children

Relation Products

- [Wood Based Activated Carbon \(Amino Acid Uses\)](#)
- [Wood Based Activated Carbon \(Food Uses\)](#)
- [Wood Based Activated Carbon \(Medical Uses\)](#)
- [Wood Based Activated Carbon \(Sugar Uses\)](#)

Remark

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers' requirement and us, if there are any changes, the latest specification will be executed and confirmed in the contract.

Manage consent