

Foreverest Resources Ltd

Polymerized Rosin

FPR-115

Polymerized Rosin is a pale, acidic which composed predominately of dimeric acids derived from rosin with lesser amounts of monomeric resin acids and neutral materials of rosin origin. It has high dimmer contents, light color, high softening point and acid value, no rystallizing, low hot water dissolvable contents, good oil dissolvability and hardly changing the color of lead acetate. The high resistance to oxidation and does not crystallize from solutions or from solid compositions. It is compatible with many natural and synthetic film formers and rubbers. Being an acidic resin, it reacts readily with polyalcohols or hydrated lime to yield high melting derivatives.

Substance Identification

Synonyms

CAS

N/A

EINECS	500-163-2
FEMA	N/A
HS.CODE	380690
Molecular Formula	N/A
Molecular Weight	N/A

Application & Uses

- Used as tackifier for industries
- Used as material for preparation of rosin based functional material

Sales Specification

ITEM	VALUE
Appearance	transparent solid
Acid Value, mgKOH/g	145
Colour, Gardner	≤10
Dissolvable Content in Hot Water, %	≤0.20

ITEM	VALUE
Softening Point, R&B, °C	110~120
Undissolved Content in Alcohol, %	≤0.030

Similar Specs

[Polymerized Rosin](#)

[Polymerized Rosin](#)

Package

- Galvanized Iron Drum, 225kg net each

GHS Hazard Statements

No GHS data available

Storage

- avoid contact with light
- keep separated from incompatible substances
- store and handle in accordance with all current regulations and standards
- store in a cool, dry place
- store in a tightly closed container

Relation Products

- [Polymerized Ester Gum](#)
- [Gum Rosin](#)
- [Rosin Modified Phenolic Resin](#)

Remark

— DISCLAIMER —

The above information is believed to be accurate and represents the best explanation currently available to us. However, no liability is assumed for any consequences arising from the use of this content. The technical standards for our products are developed and updated jointly by our customers and ourselves; where any changes occur, the latest specification shall prevail and will be confirmed in the relevant contract. All suggestions and data provided are based on information we consider to be reliable and are offered in good faith, but without any guarantee, as the conditions and methods of use of our products are beyond our control. Foreverest® makes no warranties, whether express or implied, regarding the accuracy, completeness or suitability of this information, and expressly disclaims any implied warranty of fitness for a particular purpose. Prospective users should conduct their own tests and evaluations to determine the suitability of Foreverest® materials and any recommendations for their intended applications before adoption, and, where appropriate, should obtain confirmation or approval from the relevant regulatory authorities. Any references in this page to patents or patented technologies, including

descriptive material derived from patents or citations of specific patent numbers, are provided for information only. They must not be interpreted as a recommendation to use our products in a manner that could infringe any third-party patent, nor as a grant of any licence or permission to use patents owned by Foreverest®.

Manage consent